

Ground Gas Solutions  
Pythia House (Unit 10)  
Bamford Business Park  
Hibbert Street  
Stockpot  
SK4 1PL



<b>Attention :</b>	Matt Askin
<b>Date :</b>	11th November, 2019
<b>Your reference :</b>	GG51920
<b>Our reference :</b>	Test Report 19/17860 Batch 1
<b>Location :</b>	Balcombe
<b>Date samples received :</b>	1st November, 2019
<b>Status :</b>	Final report
<b>Issue :</b>	1

Two samples were received for analysis on 1st November, 2019 of which two were scheduled for analysis. Please find attached our Test Report which should be read with notes at the end of the report and should include all sections if reproduced. Interpretations and opinions are outside the scope of any accreditation, and all results relate only to samples supplied.

All analysis is carried out on as received samples and reported on a dry weight basis unless stated otherwise. Results are not surrogate corrected.

**Authorised By:**



**Phil Sommerton BSc**  
Senior Project Manager

Please include all sections of this report if it is reproduced

# Element Materials Technology

**Client Name:** Ground Gas Solutions  
**Reference:** GGS1920  
**Location:** Balcombe  
**Contact:** Matt Askin  
**EMT Job No:** 19/17860

**Report :** Liquid

**Liquids/products:** V=40ml vial, G=glass bottle, P=plastic bottle  
 H=H<sub>2</sub>SO<sub>4</sub>, Z=ZnAc, N=NaOH, HN=HNO<sub>3</sub>

EMT Sample No.	1-7	8-14									LOD/LOR	Units	Method No.
	Sample ID	BALMW PRE-PURGE											
Depth													
COC No / misc													
Containers	V H HN P BOD G	V H HN P BOD G											
Sample Date	31/10/2019	31/10/2019											
Sample Type	Ground Water	Ground Water											
Batch Number	1	1											
Date of Receipt	01/11/2019	01/11/2019											
Dissolved Aluminium #	307	383									<20	ug/l	TM30/PM14
Dissolved Antimony #	<2	<2									<2	ug/l	TM30/PM14
Dissolved Arsenic #	4.5	3.5									<2.5	ug/l	TM30/PM14
Dissolved Barium #	333	231									<3	ug/l	TM30/PM14
Dissolved Beryllium	<0.5	<0.5									<0.5	ug/l	TM30/PM14
Dissolved Boron	769	789									<12	ug/l	TM30/PM14
Dissolved Cadmium #	<0.5	<0.5									<0.5	ug/l	TM30/PM14
Dissolved Calcium #	1.2	1.0									<0.2	mg/l	TM30/PM14
Total Dissolved Chromium #	<1.5	<1.5									<1.5	ug/l	TM30/PM14
Dissolved Cobalt #	<2	<2									<2	ug/l	TM30/PM14
Dissolved Copper #	<7	<7									<7	ug/l	TM30/PM14
Total Dissolved Iron #	136	170									<20	ug/l	TM30/PM14
Dissolved Lead #	<5	<5									<5	ug/l	TM30/PM14
Dissolved Lithium	<5	<5									<5	ug/l	TM30/PM14
Dissolved Magnesium #	0.2	0.2									<0.1	mg/l	TM30/PM14
Dissolved Manganese #	8	7									<2	ug/l	TM30/PM14
Dissolved Mercury #	<1	<1									<1	ug/l	TM30/PM14
Dissolved Molybdenum #	<2	<2									<2	ug/l	TM30/PM14
Dissolved Nickel #	<2	<2									<2	ug/l	TM30/PM14
Dissolved Potassium #	0.6	0.7									<0.1	mg/l	TM30/PM14
Dissolved Selenium #	<3	<3									<3	ug/l	TM30/PM14
Dissolved Sodium #	172.1	173.4									<0.1	mg/l	TM30/PM14
Dissolved Strontium	31	26									<5	ug/l	TM30/PM14
Dissolved Tin	<5	<5									<5	ug/l	TM30/PM14
Dissolved Vanadium #	<1.5	<1.5									<1.5	ug/l	TM30/PM14
Dissolved Zinc #	5	<3									<3	ug/l	TM30/PM14
MTBE #	<5	<5									<5	ug/l	TM31/PM12
Benzene #	<5	<5									<5	ug/l	TM31/PM12
Toluene #	<5	<5									<5	ug/l	TM31/PM12
Ethylbenzene #	<5	<5									<5	ug/l	TM31/PM12
m/p-Xylene #	<5	<5									<5	ug/l	TM31/PM12
o-Xylene #	<5	<5									<5	ug/l	TM31/PM12

Please see attached notes for all abbreviations and acronyms



# Element Materials Technology

## Notification of Deviating Samples

**Client Name:** Ground Gas Solutions  
**Reference:** GGS1920  
**Location:** Balcombe  
**Contact:** Matt Askin

**Matrix : Liquid**

EMT Job No.	Batch	Sample ID	Depth	EMT Sample No.	Analysis	Reason
19/17860	1	BALMW PRE-PURGE		1-7	BOD	Sample holding time exceeded

Please note that only samples that are deviating are mentioned in this report. If no samples are listed it is because none were deviating.  
 Only analyses which are accredited are recorded as deviating if set criteria are not met.

# NOTES TO ACCOMPANY ALL SCHEDULES AND REPORTS

EMT Job No.: 19/17860

## SOILS

Please note we are only MCERTS accredited (UK soils only) for sand, loam and clay and any other matrix is outside our scope of accreditation.

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation has been performed on clay, sand and loam, only samples that are predominantly these matrices, or combinations of them will be within our MCERTS scope. If samples are not one of a combination of the above matrices they will not be marked as MCERTS accredited.

It is assumed that you have taken representative samples on site and require analysis on a representative subsample. Stones will generally be included unless we are requested to remove them.

All samples will be discarded one month after the date of reporting, unless we are instructed to the contrary.

If you have not already done so, please send us a purchase order if this is required by your company.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

All analysis is reported on a dry weight basis unless stated otherwise. Limits of detection for analyses carried out on as received samples are not moisture content corrected. Results are not surrogate corrected. Samples are dried at 35°C ±5°C unless otherwise stated. Moisture content for CEN Leachate tests are dried at 105°C ±5°C.

Where Mineral Oil or Fats, Oils and Grease is quoted, this refers to Total Aliphatics C10-C40.

Where a CEN 10:1 ZERO Headspace VOC test has been carried out, a 10:1 ratio of water to wet (as received) soil has been used.

% Asbestos in Asbestos Containing Materials (ACMs) is determined by reference to HSG 264 The Survey Guide - Appendix 2 : ACMs in buildings listed in order of ease of fibre release.

Sufficient amount of sample must be received to carry out the testing specified. Where an insufficient amount of sample has been received the testing may not meet the requirements of our accredited methods, as such accreditation may be removed.

Negative Neutralization Potential (NP) values are obtained when the volume of NaOH (0.1N) titrated (pH 8.3) is greater than the volume of HCl (1N) to reduce the pH of the sample to 2.0 - 2.5. Any negative NP values are corrected to 0.

The calculation of Pyrite content assumes that all oxidisable sulphides present in the sample are pyrite. This may not be the case. The calculation may be an overestimate when other sulphides such as Barite (Barium Sulphate) are present.

## WATERS

Please note we are not a UK Drinking Water Inspectorate (DWI) Approved Laboratory .

ISO17025 accreditation applies to surface water and groundwater and usually one other matrix which is analysis specific, any other liquids are outside our scope of accreditation.

As surface waters require different sample preparation to groundwaters the laboratory must be informed of the water type when submitting samples.

Where Mineral Oil or Fats, Oils and Grease is quoted, this refers to Total Aliphatics C10-C40.

## DEVIATING SAMPLES

All samples should be submitted to the laboratory in suitable containers with sufficient ice packs to sustain an appropriate temperature for the requested analysis. The temperature of sample receipt is recorded on the confirmation schedules in order that the client can make an informed decision as to whether testing should still be undertaken.

## SURROGATES

Surrogate compounds are added during the preparation process to monitor recovery of analytes. However low recovery in soils is often due to peat, clay or other organic rich matrices. For waters this can be due to oxidants, surfactants, organic rich sediments or remediation fluids. Acceptable limits for most organic methods are 70 - 130% and for VOCs are 50 - 150%. When surrogate recoveries are outside the performance criteria but the associated AQC passes this is assumed to be due to matrix effect. Results are not surrogate corrected.

## DILUTIONS

A dilution suffix indicates a dilution has been performed and the reported result takes this into account. No further calculation is required.

## BLANKS

Where analytes have been found in the blank, the sample will be treated in accordance with our laboratory procedure for dealing with contaminated blanks.

## NOTE

Data is only reported if the laboratory is confident that the data is a true reflection of the samples analysed. Data is only reported as accredited when all the requirements of our Quality System have been met. In certain circumstances where all the requirements of the Quality System have not been met, for instance if the associated AQC has failed, the reason is fully investigated and documented. The sample data is then evaluated alongside the other quality control checks performed during analysis to determine its suitability. Following this evaluation, provided the sample results have not been effected, the data is reported but accreditation is removed. It is a UKAS requirement for data not reported as accredited to be considered indicative only, but this does not mean the data is not valid.

Where possible, and if requested, samples will be re-extracted and a revised report issued with accredited results. Please do not hesitate to contact the laboratory if further details are required of the circumstances which have led to the removal of accreditation.

Please include all sections of this report if it is reproduced

**REPORTS FROM THE SOUTH AFRICA LABORATORY**

Any method number not prefixed with SA has been undertaken in our UK laboratory unless reported as subcontracted.

**Measurement Uncertainty**

Measurement uncertainty defines the range of values that could reasonably be attributed to the measured quantity. This range of values has not been included within the reported results. Uncertainty expressed as a percentage can be provided upon request.

**ABBREVIATIONS and ACRONYMS USED**

#	ISO17025 (UKAS Ref No. 4225) accredited - UK.
SA	ISO17025 (SANAS Ref No.T0729) accredited - South Africa
B	Indicates analyte found in associated method blank.
DR	Dilution required.
M	MCERTS accredited.
NA	Not applicable
NAD	No Asbestos Detected.
ND	None Detected (usually refers to VOC and/SVOC TICs).
NDP	No Determination Possible
SS	Calibrated against a single substance
SV	Surrogate recovery outside performance criteria. This may be due to a matrix effect.
W	Results expressed on as received basis.
+	AQC failure, accreditation has been removed from this result, if appropriate, see 'Note' on previous page.
>>	Results above calibration range, the result should be considered the minimum value. The actual result could be significantly higher, this result is not accredited.
*	Analysis subcontracted to an Element Materials Technology approved laboratory.
AD	Samples are dried at 35°C ±5°C
CO	Suspected carry over
LOD/LOR	Limit of Detection (Limit of Reporting) in line with ISO 17025 and MCERTS
ME	Matrix Effect
NFD	No Fibres Detected
BS	AQC Sample
LB	Blank Sample
N	Client Sample
TB	Trip Blank Sample
OC	Outside Calibration Range

EMT Job No: 19/17860

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS/S ANAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM5	Modified 8015B method for the determination of solvent Extractable Petroleum Hydrocarbons (EPH) within the range C8-C40 by GCFID. For waters the solvent extracts dissolved phase plus a sheen if present.	PM16/PM30	Fractionation into aliphatic and aromatic fractions using a Rapid Trace SPE/Water samples are extracted with solvent using a magnetic stirrer to create a vortex.	Yes			
TM5/TM36	please refer to TM5 and TM36 for method details	PM12/PM16/PM30	please refer to PM16/PM30 and PM12 for method details	Yes			
TM20	Modified BS 1377-3: 1990/USEPA 160.3 Gravimetric determination of Total Dissolved Solids/Total Solids	PM0	No preparation is required.	Yes			
TM25	Determinaion of Dissolved Methane, Ethane and Ethene by Headspace GC-FID	PM0	No preparation is required.				
TM25	Determinaion of Dissolved Methane, Ethane and Ethene by Headspace GC-FID	PM0	No preparation is required.	Yes			
TM30	Determination of Trace Metal elements by ICP-OES (Inductively Coupled Plasma - Optical Emission Spectrometry). Modified US EPA Method 200.7, 6010B and BS EN ISO 11885 2009	PM14	Analysis of waters and leachates for metals by ICP OES/ICP MS. Samples are filtered for dissolved metals and acidified if required.				
TM30	Determination of Trace Metal elements by ICP-OES (Inductively Coupled Plasma - Optical Emission Spectrometry). Modified US EPA Method 200.7, 6010B and BS EN ISO 11885 2009	PM14	Analysis of waters and leachates for metals by ICP OES/ICP MS. Samples are filtered for dissolved metals and acidified if required.	Yes			
TM31	Modified USEPA 8015B. Determination of Methylterbutylether, Benzene, Toluene, Ethylbenzene and Xylene by headspace GC-FID.	PM12	Modified US EPA method 5021. Preparation of solid and liquid samples for GC headspace analysis.	Yes			
TM36	Modified US EPA method 8015B. Determination of Gasoline Range Organics (GRO) in the carbon chain range of C4-12 by headspace GC-FID. MTBE by GCFID co-elutes with 3-methylpentane if present and therefore can give a false positive. Positive MTBE results can be confirmed using GCMS.	PM12	Modified US EPA method 5021. Preparation of solid and liquid samples for GC headspace analysis.	Yes			
TM37	Modified methods USEPA 160.2, EN872:2005 and SMWW 2540D. Gravimetric determination of Total Suspended Solids. Sample is filtered through a 1.5um pore size glass fibre filter and the resulting residue is dried and weighed.	PM0	No preparation is required.	Yes			

EMT Job No: 19/17860

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS/S ANAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM38	Soluble Ion analysis using Discrete Analyser. Modified US EPA methods 325.2 (Chloride), 375.4 (Sulphate), 365.2 (o-Phosphate), 353.1 (TON), 354.1 (Nitrite), 350.1 (NH4+) comparable to BS ISO 15923-1, 7196A (Hex Cr)	PM0	No preparation is required.	Yes			
TM57	Modified US EPA Method 410.4. Comparable with ISO 15705:2002. Chemical Oxygen Demand is determined by hot digestion with Potassium Dichromate and measured spectrophotometrically.	PM0	No preparation is required.	Yes			
TM58	APHA Standard methods for the examination of water and waste water (21st ed.) 5210B. Comparable with ISO 5815:1989. Measurement of Biochemical Oxygen Demand. When cBOD (Carbonaceous BOD) is requested a nitrification inhibitor is added which prevents the oxidation of reduced forms of nitrogen, such as ammonia, nitrite and organic nitrogen which exert a nitrogenous demand. Determination of Dissolved Oxygen using the Hach HQ30D Oxygen Meter.	PM0	No preparation is required.	Yes			
TM64	Determination of the salinity of liquid samples using a salinity conductivity meter.	PM0	No preparation is required.				
TM73	Modified US EPA methods 150.1 and 9045D and BS1377:1990. Determination of pH by Metrohm automated probe analyser.	PM0	No preparation is required.	Yes			