



Exova Jones Environmental

Registered Address : Exova (UK) Ltd, Lochend Industrial Estate, Newbridge, Midlothian, EH28 8PL

Unit 3 Deeside Point
Zone 3
Deeside Industrial Park
Deeside
CH5 2UA

Ground Gas Solutions
Greenheys
Manchester Science Park
Pencroft Way
Manchester
M15 6JJ

Tel: +44 (0) 1244 833780

Fax: +44 (0) 1244 833781



Attention : Joao Dyer
Date : 13th February, 2018
Your reference : GGS1279
Our reference : Test Report 18/1326 Batch 1
Location : Balcombe
Date samples received : 31st January, 2018
Status : Final report
Issue : 1

Seven samples were received for analysis on 31st January, 2018 of which seven were scheduled for analysis. Please find attached our Test Report which should be read with notes at the end of the report and should include all sections if reproduced. Interpretations and opinions are outside the scope of any accreditation, and all results relate only to samples supplied.

All analysis is carried out on as received samples and reported on a dry weight basis unless stated otherwise. Results are not surrogate corrected.

Compiled By:

Bruce Leslie
Project Co-ordinator

NOTES TO ACCOMPANY ALL SCHEDULES AND REPORTS

JE Job No.: 18/1326

SOILS

Please note we are only MCERTS accredited (UK soils only) for sand, loam and clay and any other matrix is outside our scope of accreditation.

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation has been performed on clay, sand and loam, only samples that are predominantly these matrices, or combinations of them will be within our MCERTS scope. If samples are not one of a combination of the above matrices they will not be marked as MCERTS accredited.

It is assumed that you have taken representative samples on site and require analysis on a representative subsample. Stones will generally be included unless we are requested to remove them.

All samples will be discarded one month after the date of reporting, unless we are instructed to the contrary.

If you have not already done so, please send us a purchase order if this is required by your company.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

All analysis is reported on a dry weight basis unless stated otherwise. Results are not surrogate corrected. Samples are dried at 35°C ±5°C unless otherwise stated. Moisture content for CEN Leachate tests are dried at 105°C ±5°C.

Where Mineral Oil or Fats, Oils and Grease is quoted, this refers to Total Aliphatics C10-C40.

Where a CEN 10:1 ZERO Headspace VOC test has been carried out, a 10:1 ratio of water to wet (as received) soil has been used.

% Asbestos in Asbestos Containing Materials (ACMs) is determined by reference to HSG 264 The Survey Guide - Appendix 2 : ACMs in buildings listed in order of ease of fibre release.

Negative Neutralization Potential (NP) values are obtained when the volume of NaOH (0.1N) titrated (pH 8.3) is greater than the volume of HCl (1N) to reduce the pH of the sample to 2.0 - 2.5. Any negative NP values are corrected to 0.

The calculation of Pyrite content assumes that all oxidisable sulphides present in the sample are pyrite. This may not be the case. The calculation may be an overestimate when other sulphides such as Barite (Barium Sulphate) are present.

WATERS

Please note we are not a UK Drinking Water Inspectorate (DWI) Approved Laboratory .

ISO17025 accreditation applies to surface water and groundwater and usually one other matrix which is analysis specific, any other liquids are outside our scope of accreditation.

As surface waters require different sample preparation to groundwaters the laboratory must be informed of the water type when submitting samples.

Where Mineral Oil or Fats, Oils and Grease is quoted, this refers to Total Aliphatics C10-C40.

DEVIATING SAMPLES

Samples must be received in a condition appropriate to the requested analyses. All samples should be submitted to the laboratory in suitable containers with sufficient ice packs to sustain an appropriate temperature for the requested analysis. If this is not the case you will be informed and any test results that may be compromised highlighted on your deviating samples report.

SURROGATES

Surrogate compounds are added during the preparation process to monitor recovery of analytes. However low recovery in soils is often due to peat, clay or other organic rich matrices. For waters this can be due to oxidants, surfactants, organic rich sediments or remediation fluids. Acceptable limits for most organic methods are 70 - 130% and for VOCs are 50 - 150%. When surrogate recoveries are outside the performance criteria but the associated AQC passes this is assumed to be due to matrix effect. Results are not surrogate corrected.

DILUTIONS

A dilution suffix indicates a dilution has been performed and the reported result takes this into account. No further calculation is required.

BLANKS

Where analytes have been found in the blank, the sample will be treated in accordance with our laboratory procedure for dealing with contaminated blanks.

NOTE

Data is only reported if the laboratory is confident that the data is a true reflection of the samples analysed. Data is only reported as accredited when all the requirements of our Quality System have been met. In certain circumstances where all the requirements of the Quality System have not been met, for instance if the associated AQC has failed, the reason is fully investigated and documented. The sample data is then evaluated alongside the other quality control checks performed during analysis to determine its suitability. Following this evaluation, provided the sample results have not been effected, the data is reported but accreditation is removed. It is a UKAS requirement for data not reported as accredited to be considered indicative only, but this does not mean the data is not valid.

Where possible, and if requested, samples will be re-extracted and a revised report issued with accredited results. Please do not hesitate to contact the laboratory if further details are required of the circumstances which have led to the removal of accreditation.

REPORTS FROM THE SOUTH AFRICA LABORATORY

Any method number not prefixed with SA has been undertaken in our UK laboratory unless reported as subcontracted.

Please include all sections of this report if it is reproduced

All solid results are expressed on a dry weight basis unless stated otherwise.

ABBREVIATIONS and ACRONYMS USED

| | |
|---------|--|
| # | ISO17025 (UKAS Ref No. 4225) accredited - UK. |
| SA | ISO17025 (SANAS Ref No.T0729) accredited - South Africa. |
| B | Indicates analyte found in associated method blank. |
| DR | Dilution required. |
| M | MCERTS accredited. |
| NA | Not applicable |
| NAD | No Asbestos Detected. |
| ND | None Detected (usually refers to VOC and/SVOC TICs). |
| NDP | No Determination Possible |
| SS | Calibrated against a single substance |
| SV | Surrogate recovery outside performance criteria. This may be due to a matrix effect. |
| W | Results expressed on as received basis. |
| + | AQC failure, accreditation has been removed from this result, if appropriate, see 'Note' on previous page. |
| ++ | Result outside calibration range, results should be considered as indicative only and are not accredited. |
| * | Analysis subcontracted to a Jones Environmental approved laboratory. |
| AD | Samples are dried at 35°C ±5°C |
| CO | Suspected carry over |
| LOD/LOR | Limit of Detection (Limit of Reporting) in line with ISO 17025 and MCERTS |
| ME | Matrix Effect |
| NFD | No Fibres Detected |
| BS | AQC Sample |
| LB | Blank Sample |
| N | Client Sample |
| TB | Trip Blank Sample |
| OC | Outside Calibration Range |
| AA | x5 Dilution |

JE Job No: 18/1326

| Test Method No. | Description | Prep Method No. (if appropriate) | Description | ISO 17025 (UKAS/S ANAS) | MCERTS (UK soils only) | Analysis done on As Received (AR) or Dried (AD) | Reported on dry weight basis |
|-----------------|---|----------------------------------|---|-------------------------|------------------------|---|------------------------------|
| TM0 | Not available | PM0 | No preparation is required. | | | | |
| TM5 | Modified USEPA 8015B method for the determination of solvent Extractable Petroleum Hydrocarbons (EPH) with carbon banding within the range C8-C40 GC-FID. | PM30 | Water samples are extracted with solvent using a magnetic stirrer to create a vortex. | Yes | | | |
| TM5/TM36 | please refer to TM5 and TM36 for method details | PM30/PM12 | CWG GC-FID | Yes | | | |
| TM20 | Modified BS 1377-3: 1990/USEPA 160.3 Gravimetric determination of Total Dissolved Solids/Total Solids | PM0 | No preparation is required. | Yes | | | |
| TM27 | Modified US EPA method 9056.Determination of water soluble anions using Dionex (Ion-Chromatography). | PM0 | No preparation is required. | | | | |
| TM30 | Determination of Trace Metal elements by ICP-OES (Inductively Coupled Plasma - Optical Emission Spectrometry). Modified US EPA Method 200.7, 6010B and BS EN ISO 11885 2009 | PM14 | Analysis of waters and leachates for metals by ICP OES/ICP MS. Samples are filtered for dissolved metals and acidified if required. | | | | |
| TM30 | Determination of Trace Metal elements by ICP-OES (Inductively Coupled Plasma - Optical Emission Spectrometry). Modified US EPA Method 200.7, 6010B and BS EN ISO 11885 2009 | PM14 | Analysis of waters and leachates for metals by ICP OES/ICP MS. Samples are filtered for dissolved metals and acidified if required. | Yes | | | |
| TM31 | Modified USEPA 8015B. Determination of Methylterbutylether, Benzene, Toluene, Ethylbenzene and Xylene by headspace GC-FID. | PM12 | Modified US EPA method 5021. Preparation of solid and liquid samples for GC headspace analysis. | Yes | | | |
| TM36 | Modified US EPA method 8015B. Determination of Gasoline Range Organics (GRO) in the carbon chain range of C4-12 by headspace GC-FID. | PM12 | Modified US EPA method 5021. Preparation of solid and liquid samples for GC headspace analysis. | Yes | | | |
| TM37 | Modified USEPA 160.2 .Gravimetric determination of Total Suspended Solids. Sample is filtered and the resulting residue is dried and weighed. | PM0 | No preparation is required. | Yes | | | |

JE Job No: 18/1326

| Test Method No. | Description | Prep Method No. (if appropriate) | Description | ISO 17025 (UKAS/S ANAS) | MCERTS (UK soils only) | Analysis done on As Received (AR) or Dried (AD) | Reported on dry weight basis |
|-----------------|---|----------------------------------|-----------------------------|-------------------------|------------------------|---|------------------------------|
| TM38 | Soluble Ion analysis using the Thermo Aquakem Photometric Automatic Analyser. Modified US EPA methods 325.2, 375.4, 365.2, 353.1, 354.1 | PM0 | No preparation is required. | Yes | | | |
| TM57 | Modified US EPA Method 410.4. Chemical Oxygen Demand is determined by hot digestion with Potassium Dichromate and measured spectrophotometrically. | PM0 | No preparation is required. | Yes | | | |
| TM58 | Modified USEPA methods 405.1 and BS 5667-3. Measurement of Biochemical Oxygen Demand. When cBOD (Carbonaceous BOD) is requested a nitrification inhibitor is added which prevents the oxidation of reduced forms of nitrogen, such as ammonia, nitrite and organic nitrogen which exert a nitrogenous demand. | PM0 | No preparation is required. | Yes | | | |
| TM64 | Determination of the salinity of liquid samples using a salinity conductivity meter. | PM0 | No preparation is required. | | | | |
| TM73 | Modified US EPA methods 150.1 and 9045D and BS1377:1990. Determination of pH by Metrohm automated probe analyser. | PM0 | No preparation is required. | Yes | | | |
| TM75 | Modified US EPA method 310.1. Determination of Alkalinity by Metrohm automated titration analyser. | PM0 | No preparation is required. | Yes | | | |
| TM76 | Modified US EPA method 120.1. Determination of Specific Conductance by Metrohm automated probe analyser. | PM0 | No preparation is required. | Yes | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |



hallanalytical

a Crawford Scientific company

CERTIFICATE OF ANALYSIS

Water Sample Analysis

| | |
|----------------------|--------------------------------|
| Hall Study Reference | HAL18-053 |
| Sample Description | Water Samples |
| Submitting Client | J. Dyer |
| Client Reference | PO372 |
| Date(s) Analysed | 14 th February 2018 |
| Date of Certificate | 15 th February 2018 |

Determination of Methane and Carbon Dioxide in water (All values in mg/L represent the TOTAL gas in the water).

| Hall ID | Client ID | Date Sampled | Sample Type | CH ₄ | C ₂ H ₆ | CO ₂ |
|---------|----------------------|--------------|-------------|-----------------|-------------------------------|-----------------|
| H75133 | BALMW01 – Pre-Purge | 30/01/18 | Water | 6.75 | <0.01 | 5.92 |
| H75134 | BALMW01 – Post Purge | 30/01/18 | Water | 13.4 | 1.53 | 1.13 |

No other hydrocarbons (C₃-C₆) were detected

Henry's constants used Methane: 41300 Carbon dioxide: 1630
Amount of ethane based from methane response

For the Attention of: Joao Dyer
Ground Gas
Greenheys
Manchester Science Park
Pencroft Way
Manchester
M15 6JJ

Authorised on behalf of Hall Analytical Laboratories Ltd

M. L. Kimber

Unit A, Millbrook Business Centre, Floats Road, Manchester. M23 9YJ
Tel: +44 (0)161 2867889 Fax: +44 (0)161 2867676 www.hallanalytical.co.uk
VAT Reg. No. 603 5991 38 Company Registration (UK) 2759064