



Jones Environmental Laboratory

Registered Address : Unit 3 Deeside Point, Zone 3, Deeside Industrial Park, Deeside, CH5 2UA. UK

Unit 3 Deeside Point
Zone 3
Deeside Industrial Park
Deeside
CH5 2UA

Ground Gas Solutions
Greenheys
Manchester Science Park
Pencroft Way
Manchester
M15 6JJ

Tel: +44 (0) 1244 833780

Fax: +44 (0) 1244 833781



Attention : Joao Dyer
Date : 14th July, 2015
Your reference : GGS617
Our reference : Test Report 15/9575 Batch 1
Location : Balcombe
Date samples received : 3rd July, 2015
Status : Final report
Issue : 1

Two samples were received for analysis on 3rd July, 2015 of which two were scheduled for analysis. Please find attached our Test Report which should be read with notes at the end of the report and should include all sections if reproduced. Interpretations and opinions are outside the scope of any accreditation, and all results relate only to samples supplied.

All analysis is carried out on as received samples and reported on a dry weight basis unless stated otherwise. Results are not surrogate corrected.

Compiled By:

A handwritten signature in black ink, appearing to read "Phil".

Phil Sommerton BSc
Project Manager

Client Name: Ground Gas Solutions
 Reference: GGS617
 Location: Balcombe
 Contact: Joao Dyer
 JE Job No.: 15/9575

Report : Liquid

Liquids/products: V=40ml vial, G=glass bottle, P=plastic bottle
 H=H₂SO₄, Z=ZnAc, N=NaOH, HN=HNO₃

J E Sample No.	1-6	7-12												
Sample ID	BALMW01-1	BALMW01-2												
Depth														
COC No / misc														
Containers	V H P BOD G	V H P BOD G												
Sample Date	02/07/2015	02/07/2015												
Sample Type	Ground Water	Ground Water												
Batch Number	1	1												
Date of Receipt	03/07/2015	03/07/2015												
										LOD/LOR	Units	Method No.		
Dissolved Arsenic #	6.2	<2.5								<2.5	ug/l	TM30/PM14		
Dissolved Barium #	311	386								<3	ug/l	TM30/PM14		
Dissolved Boron	925	851								<12	ug/l	TM30/PM14		
Dissolved Cadmium #	<0.5	<0.5								<0.5	ug/l	TM30/PM14		
Dissolved Calcium #	1.5	2.0								<0.2	mg/l	TM30/PM14		
Total Dissolved Chromium #	<1.5	<1.5								<1.5	ug/l	TM30/PM14		
Dissolved Cobalt #	<2	<2								<2	ug/l	TM30/PM14		
Dissolved Copper #	<7	<7								<7	ug/l	TM30/PM14		
Total Dissolved Iron #	<20	<20								<20	ug/l	TM30/PM14		
Dissolved Lead #	<5	<5								<5	ug/l	TM30/PM14		
Dissolved Magnesium #	0.2	0.2								<0.1	mg/l	TM30/PM14		
Dissolved Manganese #	14	9								<2	ug/l	TM30/PM14		
Dissolved Mercury #	<1	<1								<1	ug/l	TM30/PM14		
Dissolved Molybdenum #	<2	<2								<2	ug/l	TM30/PM14		
Dissolved Nickel #	<2	<2								<2	ug/l	TM30/PM14		
Dissolved Potassium #	1.1	0.8								<0.1	mg/l	TM30/PM14		
Dissolved Selenium #	<3	<3								<3	ug/l	TM30/PM14		
Dissolved Sodium #	238.2 ^{AA}	248.4 ^{AA}								<0.1	mg/l	TM30/PM14		
Dissolved Strontium	37	46								<5	ug/l	TM30/PM14		
Dissolved Vanadium #	<1.5	<1.5								<1.5	ug/l	TM30/PM14		
Dissolved Zinc #	5	<3								<3	ug/l	TM30/PM14		
TPH CWG														
Aliphatics														
>C5-C6 #	<5	<5								<5	ug/l	TM36/PM12		
>C6-C8 #	<5	<5								<5	ug/l	TM36/PM12		
>C8-C10 #	<5	<5								<5	ug/l	TM36/PM12		
>C10-C12 #	<5	<5								<5	ug/l	TM5/PM30		
>C12-C16 #	<10	<10								<10	ug/l	TM5/PM30		
>C16-C21 #	<10	<10								<10	ug/l	TM5/PM30		
>C21-C35 #	<10	<10								<10	ug/l	TM5/PM30		
Total aliphatics C5-35 #	<10	<10								<10	ug/l	TM5/TM36/PM30		
Aromatics														
>C5-EC7 #	<5	<5								<5	ug/l	TM36/PM12		
>EC7-EC8 #	<5	<5								<5	ug/l	TM36/PM12		
>EC8-EC10 #	<5	<5								<5	ug/l	TM36/PM12		
>EC10-EC12 #	<5	<5								<5	ug/l	TM5/PM30		
>EC12-EC16 #	<10	<10								<10	ug/l	TM5/PM30		
>EC16-EC21 #	<10	<10								<10	ug/l	TM5/PM30		
>EC21-EC35 #	<10	<10								<10	ug/l	TM5/PM30		
Total aromatics C5-35 #	<10	<10								<10	ug/l	TM5/PM30		
Total aliphatics and aromatics(C5-35) #	<10	<10								<10	ug/l	TM5/TM36/PM30		
MTBE #	<5	<5								<5	ug/l	TM36/PM12		

Please see attached notes for all abbreviations and acronyms

NOTES TO ACCOMPANY ALL SCHEDULES AND REPORTS

JE Job No.: 15/9575

SOILS

Please note we are only MCERTS accredited (UK soils only) for sand, loam and clay and any other matrix is outside our scope of accreditation.

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation has been performed on clay, sand and loam, only samples that are predominantly these matrices, or combinations of them will be within our MCERTS scope. If samples are not one of a combination of the above matrices they will not be marked as MCERTS accredited.

It is assumed that you have taken representative samples on site and require analysis on a representative subsample. Stones will generally be included unless we are requested to remove them.

All samples will be discarded one month after the date of reporting, unless we are instructed to the contrary.

If you have not already done so, please send us a purchase order if this is required by your company.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

All analysis is reported on a dry weight basis unless stated otherwise. Results are not surrogate corrected. Samples are dried at 35°C ±5°C unless otherwise stated. Moisture content for CEN Leachate tests are dried at 105°C ±5°C.

Where Mineral Oil or Fats, Oils and Grease is quoted, this refers to Total Aliphatics C10-C40.

Where a CEN 10:1 ZERO Headspace VOC test has been carried out, a 10:1 ratio of water to wet (as received) soil has been used.

% Asbestos in Asbestos Containing Materials (ACMs) is determined by reference to HSG 264 The Survey Guide - Appendix 2 : ACMs in buildings listed in order of ease of fibre release.

WATERS

Please note we are not a UK Drinking Water Inspectorate (DWI) Approved Laboratory .

ISO17025 (UKAS) accreditation applies to surface water and groundwater and one other matrix which is analysis specific, any other liquids are outside our scope of accreditation.

As surface waters require different sample preparation to groundwaters the laboratory must be informed of the water type when submitting samples.

Where Mineral Oil or Fats, Oils and Grease is quoted, this refers to Total Aliphatics C10-C40.

DEVIATING SAMPLES

Samples must be received in a condition appropriate to the requested analyses. All samples should be submitted to the laboratory in suitable containers with sufficient ice packs to sustain an appropriate temperature for the requested analysis. If this is not the case you will be informed and any test results that may be compromised highlighted on your deviating samples report.

SURROGATES

Surrogate compounds are added during the preparation process to monitor recovery of analytes. However low recovery in soils is often due to peat, clay or other organic rich matrices. For waters this can be due to oxidants, surfactants, organic rich sediments or remediation fluids. Acceptable limits for most organic methods are 70 - 130% and for VOCs are 50 - 150%. When surrogate recoveries are outside the performance criteria but the associated AQC passes this is assumed to be due to matrix effect. Results are not surrogate corrected.

DILUTIONS

A dilution suffix indicates a dilution has been performed and the reported result takes this into account. No further calculation is required.

NOTE

Data is only reported if the laboratory is confident that the data is a true reflection of the samples analysed. Data is only reported as accredited when all the requirements of our Quality System have been met. In certain circumstances where all the requirements of the Quality System have not been met, for instance if the associated AQC has failed, the reason is fully investigated and documented. The sample data is then evaluated alongside the other quality control checks performed during analysis to determine its suitability. Following this evaluation, provided the sample results have not been effected, the data is reported but accreditation is removed. It is a UKAS requirement for data not reported as accredited to be considered indicative only, but this does not mean the data is not valid.

Where possible, and if requested, samples will be re-extracted and a revised report issued with accredited results. Please do not hesitate to contact the laboratory if further details are required of the circumstances which have led to the removal of accreditation.

Please include all sections of this report if it is reproduced

ABBREVIATIONS and ACRONYMS USED

#	ISO17025 (UKAS) accredited - UK.
B	Indicates analyte found in associated method blank.
DR	Dilution required.
M	MCERTS accredited.
NA	Not applicable
NAD	No Asbestos Detected.
ND	None Detected (usually refers to VOC and/SVOC TICs).
NDP	No Determination Possible
SS	Calibrated against a single substance
SV	Surrogate recovery outside performance criteria. This may be due to a matrix effect.
W	Results expressed on as received basis.
+	AQC failure, accreditation has been removed from this result, if appropriate, see 'Note' on previous page.
++	Result outside calibration range, results should be considered as indicative only and are not accredited.
*	Analysis subcontracted to a Jones Environmental approved laboratory.
AD	Samples are dried at 35°C ±5°C
CO	Suspected carry over
LOD/LOR	Limit of Detection (Limit of Reporting) in line with ISO 17025 and MCERTS
ME	Matrix Effect
NFD	No Fibres Detected
BS	AQC Sample
LB	Blank Sample
N	Client Sample
TB	Trip Blank Sample
OC	Outside Calibration Range
AA	x5 Dilution

JE Job No: 15/9575

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM0	Not available	PM0	No preparation is required.				
TM5	Modified USEPA 8015B method for the determination of solvent Extractable Petroleum Hydrocarbons (EPH) with carbon banding within the range C8-C40 GC-FID.	PM30	Water samples are extracted with solvent using a magnetic stirrer to create a vortex.	Yes			
TM5/TM36	TM005: Modified USEPA 8015B. Determination of solvent Extractable Petroleum Hydrocarbons (EPH) including column fractionation in the carbon range of C10-35 into aliphatic and aromatic fractions by GC-FID. TM036: Modified USEPA 8015B. Determination of Gasoline Range Organics (GRO) in the carbon chain range of C5-10 by headspace GC-FID.	PM30	Water samples are extracted with solvent using a magnetic stirrer to create a vortex.	Yes			
TM20	Modified USEPA 8163. Gravimetric determination of Total Dissolved Solids/Total Solids	PM0	No preparation is required.	Yes			
TM27	Modified US EPA method 9056. Determination of water soluble anions using Dionex (Ion-Chromatography).	PM0	No preparation is required.				
TM30	Determination of Trace Metal elements by ICP-OES (Inductively Coupled Plasma - Optical Emission Spectrometry). Modified US EPA Method 200.7	PM14	Analysis of waters and leachates for metals by ICP OES. Samples are filtered for dissolved metals and acidified if required.				
TM30	Determination of Trace Metal elements by ICP-OES (Inductively Coupled Plasma - Optical Emission Spectrometry). Modified US EPA Method 200.7	PM14	Analysis of waters and leachates for metals by ICP OES. Samples are filtered for dissolved metals and acidified if required.	Yes			
TM36	Modified US EPA method 8015B. Determination of Gasoline Range Organics (GRO) in the carbon chain range of C4-12 by headspace GC-FID.	PM12	Modified US EPA method 5021. Preparation of solid and liquid samples for GC headspace analysis.	Yes			
TM37	Modified USEPA 160.2. Gravimetric determination of Total Suspended Solids. Sample is filtered and the resulting residue is dried and weighed.	PM0	No preparation is required.	Yes			
TM38	Soluble Ion analysis using the Thermo Aquakem Photometric Automatic Analyser. Modified US EPA methods 325.2, 375.4, 365.2, 353.1, 354.1	PM0	No preparation is required.	Yes			

JE Job No: 15/9575

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM57	Modified US EPA Method 410.4. Chemical Oxygen Demand is determined by hot digestion with Potassium Dichromate and measured spectrophotometrically.	PM0	No preparation is required.	Yes			
TM58	Modified USEPA methods 405.1 and BS 5667-3. Measurement of Biochemical Oxygen Demand.	PM0	No preparation is required.	Yes			
TM64	Determination of the salinity of liquid samples using a salinity meter.	PM0	No preparation is required.				
TM73	Modified US EPA methods 150.1 and 9045D. Determination of pH by Metrohm automated probe analyser.	PM0	No preparation is required.	Yes			
TM75	Modified US EPA method 310.1. Determination of Alkalinity by Metrohm automated titration analyser.	PM0	No preparation is required.	Yes			
TM76	Modified US EPA method 120.1. Determination of Specific Conductance by Metrohm automated probe analyser.	PM0	No preparation is required.	Yes			